

# Topcon CR-P1

## Laser Scanner



The CR-P1 Laser Scanner is a vital tool for construction, architecture, and engineering professionals, providing accurate 3D data to optimize workflows. Available in two models - CR-P1 S (100 m range) and CR-P1 M (200 m range) - it excels at capturing high-resolution data for building design, documenting large renovation sites, and ensuring precision in construction progress and as-built plans, even in challenging environments.

- » 2 million points per second scanning speed
- » 3D accuracy: 2 mm  
Distance accuracy: 1mm
- » 2-year manufacturer warranty
- » Real-time scan registration and real-time complete dataset processing in Collage Site

Page 1/2

### Performance Specifications

	CR-P1 S	CR-P1 M
Unambiguity Interval <sup>1</sup>	614 m	614 m
<b>Range:</b>		
White, 90% Reflectivity	0.5-100 m	0.5-200 m
Dark-grey, 10% Reflectivity	0.5-100 m	0.5-150 m
Black, 2% Reflectivity	0.5-50 m	0.5-50 m
<b>Range Noise<sup>2,3</sup>:</b>		
White, 90% Reflectivity	0.1 mm @ 10 m, 0.2 mm @ 25 m	
Dark-grey, 10%	0.3 mm @ 10 m, 0.4 mm @ 25 m	
<b>Reflectivity:</b>		
Black, 2% Reflectivity	0.7 mm @ 10 m, 1.2 mm @ 25 m	
Max Speed	Up to 2 MPts/sec	
3D Accuracy <sup>4</sup>	2 mm @ 10 m, 3.5 mm @ 25 m	
Ranging Error <sup>5</sup>	±1 mm	
Angular Accuracy <sup>6</sup>	19 arcsec	
Temperature Range <sup>7</sup>	Operating: +5° to +40° C Extended Operating: -10° to +55° C Storage: -10° to +60° C	

### Additional Performance Specifications

#### Color Unit:

HDR Camera	13 MPx - 2x, 3x, 5x brackets
Parallax	Minimized due to co-axial design

#### Deflection Unit:

Field of View	300° vertical / 360° horizontal
Step Size	vertical 0.009° (40,960 Pts on 360°) horizontal 0.009° (40,960 Pts on 360°)
Max. Scan Speed	97 Hz (vertical)

#### Laser (Optical Transmitter):

Laser Class	Laser Class 1
Wavelength	1553.5 nm
Beam Divergence	0.3 mrad (1/e)
Beam Diameter at Exit	2.12 mm (1/e)

#### Data Handling and Control:

Data Storage	SATA 3.0 SSD 128 GB and SDXC™ V30 64 GB SD Card; SD3.0, UHS-I / SDXC™ / SDHC™, max. 512 GB
Scanner Control	Via touch screen display and WLAN connection

# Topcon CR-P1

## Laser Scanner

### Additional Performance Specifications

#### Interface Connection:

WLAN	IEEE 802.11 ac/a/b/g/n 2x2 MIMO, as access point or client in existing networks (2.4 and 5 GHz)
USB	USB 3 port

### Additional Features

Dual Axis Compensator	Performs a leveling of each scan with an accuracy of 19 arcsec valid within $\pm 2^\circ$
Accessory Bay	The accessory bay connects versatile accessories to the scanner
Inverse Mounting	Yes
Real-time, On-site Registration	Complete data registration on-site with Collage Site
Electronic Automation Interface	Available as option, only at point of sale
Retake Photos	Select individual photographs with unwanted objects and retake them

### General Specifications

Power Supply	19 V (external supply), 14.4 V (internal battery)
Typical Power Consumption	19 W idle, 32 W scanning, 72 W charging
Typical Battery Operation Time	About 4 hours
Typical Scan Time: From start until the scanner can be moved <sup>10</sup>	Gray scale < 1 min   HDR Colored < 1:15 min
Ingress Protection (IP) Rating Class	54
Humidity	Non-condensing
Weight	4.4 kg (including battery)
Size/Dimensions	230 x 183 x 103 mm
Calibration	Recommended annually
Manufacturer Warranty	2 year

1. @ 0.5MPts/s, depends on scanning speed
2. Ranging noise is defined as the variation of distance samples from repeated measurements of a single point at 122k Pts/sec
3. Some surfaces can lead to additional noise
4. For distances larger 25 m add 0.1 mm/m of uncertainty
5. Ranging error is defined as a systematic measurement error at around 10 m and 25 m
6. It is recommended to perform on-site compensation in the event the unit is exposed to exceptional temperature or mechanical stress
7. Low temperature operation: scanner has to be powered on while internal temperature is at or above 15° C. High temperature operation: additional accessory Thermal Cover required
8. 2x150°, homogeneous point spacing is not guaranteed
9. Ferromagnetic objects can disturb the earth magnetic field and lead to inaccurate measurements
10. Accelerated Profile with PanoCam